

AIR FILTRATION SYSTEMS



TAMA®

AERNOVA

I B E R I C A

DUCTING AND COMPONENTS



To completion of the whole supply, Tama offers a wide range of zinc-coated sheet steel pipes and fittings of various sizes and thicknesses, available in the catalogue.

DUCTING AND COMPONENTS



PIPES

Realized in zinc-coated steel sheet, with lengths from 1 m and 1.5 m. Sheet thicknesses from 6/10 to 10/10 with \varnothing 80 mm to 1000 mm. Available in smooth, flapped or flanged version.



CIRCULAR CURVE 30, 45, 60, 90 WITH SECTORS

Realized in zinc-coated steel sheet, sheet thicknesses 8/10 with \varnothing from 80 mm to 1000 mm. Available in smooth, flapped or flanged version.



1-WAY DEVIATION

Realized in zinc-coated steel sheet, with \varnothing from 80mm to 1000 mm. Available in smooth or flapped version.



CONNECTOR

Realized in zinc-coated steel sheet, sheet thicknesses from 8/10 to 15/10 with \varnothing from 80mm to 1000 mm. Available in smooth, flanged or flapped version.



CONE

Realized in zinc-coated steel sheet, sheet thicknesses from 8/10 to 15/10 with \varnothing from 80mm to 1000 mm. Available in smooth or flapped version.



4/5/6/7 HEADED OUTPUT

Realized in zinc-coated steel sheet, sheet thicknesses from 8/ with \varnothing from 180mm to 400 mm. Available in smooth, flanged or flapped version.



EXPULSION CAP WITHOUT TOP

Realized in zinc-coated steel sheet, sheet thicknesses from 8/10 to 15/10 with \varnothing from 200mm to 1000 mm. Available in smooth or flapped version.



EXPULSION CAP WITH MESH

Realized in zinc-coated steel sheet, Sheet thicknesses from 8/10 to 15/10 with \varnothing from 80mm to 1000 mm. Available in smooth, flanged or flapped version.



CHINESE STYLE EXPULSION CAP

Realized in zinc-coated steel sheet, Sheet thicknesses from 8/10 to 15/10 with \varnothing from 120mm to 1000 mm. Available in smooth or flapped version.



SOUNDPROOFING TUBE

Realized in zinc-coated steel sheet, with lengths from 1 m and 1.5 m. sheet thicknesses from 8/10 to 10/10 with \varnothing 80 mm to 1000 mm. Available in smooth, flanged or flapped version.



CIRCULAR AND LINEAR SOCKET

Realized in zinc-coated steel sheet, sheet thicknesses from 8/10 to 10/10 with \emptyset from 80 mm to 1000 mm. Available in smooth or flapped version.



ANTI-VIBRATION JOINT with PVC CANVAS

Realized in zinc-coated steel sheet, sheet thicknesses from 6/10 with \emptyset from 100 mm to 1000 mm. Available in smooth, flanged or flapped version.



CIRCULAR STOPPER

Realized in zinc-coated steel sheet, with \emptyset from 80mm to 1000 mm.



CLAMPS

Clamp for tubing, widths from 300 mm to 1400 mm.
Painted clamp for chimney, \emptyset from 300 mm to 1000 mm.



COLLARS:

PAINTED COLLAR

Realized in painted steel sheet, \emptyset from 300 mm to 1000 mm.

ZINC-COATED STEEL SHEET COLLAR

Collar realized in zinc-coated steel sheet, \emptyset from 80 mm to 400 mm.

MONO-COLLAR

Realized in zinc-coated steel sheet, \emptyset from 180 mm to 1000 mm.



FLANGES:

CIRCULAR PRESSED FLANGE

Realized in zinc-coated steel sheet, \emptyset from 80 mm to 600 mm.

CIRCULAR ANGULAR FLANGE

Realized in zinc-coated steel sheet, \emptyset from 80 mm to 600 mm.



GUILLOTINE SHUTTERS:

HAND GUILLOTINE SHUTTER

Light range: \emptyset from 80 mm to 600 mm.
Heavy-duty range: \emptyset from 350 mm to 800 mm.

PNEUMATIC GUILLOTINE SHUTTER

Light range: \emptyset from 80 mm to 300 mm.
Heavy-duty range: \emptyset from 350 mm to 800 mm.

ELECTRO-PNEUMATIC GUILLOTINE SHUTTER

Light range: \emptyset from 80 mm to 300 mm.
Heavy-duty range: \emptyset from 350 mm to 800 mm.
Realized in zinc-coated steel sheet, available in smooth, flanged or flapped version.



HAND, PNEUMATIC AND ELECTRO-PNEUMATIC BUTTERFLY SHUTTER

Realized in zinc-coated steel sheet, \emptyset from 80 mm to 600 mm.
Available in smooth, flanged or flapped version.



NON RETURN VALVE

Realized in zinc-coated steel sheet, \emptyset from 200 mm to 600 mm.
Available in smooth, flanged or flapped version.



FLOOR SUCTION OPENING

Realized in zinc-coated steel sheet, \emptyset from 120 mm to 150 mm.
Available in smooth, flanged or flapped version.



FLEXIBLE HOSE

Realized in strengthened and transparent polyurethane with steel spiral.



FLEXIBLE HOSE CLAMP

Realized in zinc-coated steel sheet, \emptyset from 60 mm to 400 mm.